

**A SYSTEM AND METHOD FOR OPTIMIZING TEMPERATURE
OPERATING RANGES FOR A THERMAL INKJET PRINTHEAD**

By Paul Crivelli, Maria Dinares, and Rosa Maria Gomez

FIELD OF THE INVENTION

The present invention generally relates to inkjet printers and in particular to a system and method for optimizing the temperature operating range of inkjet printers using pigmented ink over large print swaths with high throughput.

BACKGROUND OF THE INVENTION

Inkjet printers are commonplace in the computer field. These printers are described by W.J. Lloyd and H.T. Taub in "Ink Jet Devices," Chapter 13 of *Output Hardcopy Devices* (Ed. R.C. Durbeck and S. Sherr, San Diego: Academic Press, 1988) and U.S. Patents 4,490,728 and 4,313,684. Inkjet printers produce high quality print, are compact and portable, and print quickly and quietly because only ink strikes a printing medium, such as paper.

An inkjet printer produces a printed image by printing a pattern of individual dots at particular locations of an array defined for the printing medium. The locations are conveniently visualized as being small dots in a rectilinear array. The locations are sometimes "dot locations", "dot positions", or pixels". Pixels vary in size, the smaller the dot in the rectilinear array, means that more dots can be printed per inch of the printed medium. Smaller dots result in a more accurate rendition of the image and this in turn results in greater definition of the image. Thus, the printing operation can be viewed as the filling of a pattern of dot locations with dots of ink of specific size or from a combination of different sized dots.

Inkjet printers print dots by ejecting very small drops of ink onto the print medium and typically include a movable carriage that supports one or more print cartridges each having a printhead with a nozzle member having ink ejecting nozzles. The carriage traverses over the surface of the print medium. The width of the carriage varies among the different printers. For any line of print, the carriage may make more than one traverse and utilize a

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
223

inks, in particular, pigmented inks. If the temperature is too low the ink droplets formed will be smaller and have a lower drop-weight than that required for good image quality. As the temperature rises, the drop-weight of the ink droplet will rise. The variation in drop weight varies with the ink being used. These variations in drop-weight will cause visible hue shifts in the printed image.

The temperature will be high if the resistors fire a number of times in a short period of time. Also, if the length of the current pulse to the resistor is longer than a pre-determined limit. As the carriage traverses in a print swath, various heater elements in the array are activated. If the traverse is narrow, the mean temperature at the beginning of the traverse will be similar to the mean temperature at the conclusion, and the effect of temperature on the pass will be consistent for all ink droplets projected onto the print media. If the swath is wide, and more heater elements are activated, the mean temperature at the end of the pass may be considerably higher than at the beginning. The difference in temperature from the beginning of the pass to the end of the pass could result in variation in the drop-weight of ink droplets on the same pass. This would result in hue variation on the one line of print.

Generally, the temperature of the printhead is approximated by two measurements, the thermal sense resistor [TSR], and the digital temperature sensor [DTS]. The DTS is a point sensor located at the top of the die near a firing heating element. While this sensor more accurately reflects the temperature at that point, it does not give an accurate temperature for other heating elements on the die.

The TSR is an approximation of the mean temperature of the printhead die. It is not located adjacent to any particular heating element and reflects the temperature of the die after heat has moved from the heating elements to the TSR. There is, therefore, a delay in the temperature reported by the TSR. The longer the printhead fires, the greater will be the temperature recorded by the TSR. When the printhead has been idle, for example, at the beginning of a print pass, the temperature recorded by the TSR will be low as the die will be cool. The droplets produced at this time will be of low drop-weight. As the pass continues and the number of heating elements firing has increased, the

temperature at the TSR will have increased and the drop-weight of the ink droplets will have increased. The difference in temperature from the beginning of the pass till the end of the pass will affect the size of the ink droplets across the pass.

5 To minimize the effect of temperature variance from the beginning of printing to another point in the printing process, a warming device may be employed. A warming device is used to raise the temperature of the printhead. The printhead assembly may include a means to control the electrical current to the firing resistors so that their temperature is below the
10 threshold required to eject an ink drop. This device could be a power field effect transistor [FET]. The device provides a capability to warm the printhead assembly to the desired temperature before or during printing operations. The process is called "trickle warming" because the printhead assembly allows only a trickle of energy to flow to the firing resistors. The
15 printhead assembly temperature rises until the desired temperature is reached and the warming device is then shut off. However, these systems do not effectively control increases in the mean temperature of the die, and hence, cannot optimize the temperature operating range of the die.

20 Therefore, what is needed is a method to control and decrease the temperature difference of the printhead from the beginning of the swath to the end, when necessary. What is also needed is a printing system that controls the temperature of the die by measuring and incorporating the temperatures of the heating elements in the printhead die and using these temperatures to preheat the die. What is additionally needed is a feedback loop to turn off
25 these heating elements once an optimal operating temperature has been attained. What is further needed is a system that will produce a more uniform dot pattern on each print pass of the printhead, an improved quality of ink droplet size and a better image quality with a die temperature controller.

SUMMARY OF THE INVENTION

30 To overcome the limitations in the prior art described above, and to overcome other limitations that will become apparent upon reading and understanding the present specification, the present invention is embodied in a

system and method for optimizing the temperature operating range for a thermal inkjet printhead using pigmented ink over large print swaths with high throughput.

5 The printhead assembly includes connection and processing circuitry, a printhead body, ink channels, a substrate, such as a semiconductor wafer (commonly referred to as a die), a nozzle member and a barrier layer located between the wafer and nozzle member. The nozzle member has heating elements in arrays, as well as plural nozzles coupled to respective ink channels and is secured at a predefined location to the printhead body with a suitable adhesive layer. The printhead also includes a controller, which can be an integrated circuit processor, a printer driver, firmware or the like for controlling an increase in the mean temperature of the die through a programmable feedback loop. The loop activates the heating elements and therefore increases the baseline temperature of the die before printing, and in turn decreases the temperature differential between the baseline temperature and the mean temperature of the die.

10 The controller can be defined in the integrated circuit as receiving the temperature of a digital temperature sensor (DTS) before printing begins, comparing this temperature with the set point for printing, initiating heating elements if the temperature is below the printing threshold, and turning off those heating elements when the threshold temperature of the die has been reached. The controller can be created by any suitable integrated circuit manufacturing or programming process.

15 20 The controller maintains the mean temperature of the die at a temperature that is within a predefined range of an optimal temperature for the production of a droplet of ink. There are pens for black inks and colored inks. Each pen will have a DTS feedback loop. Consequently, the present invention aids in controlling the temperature of specific sections of the die and the baseline temperature of the nozzle chambers associated with that section. 25 30 This will result in improved conformity of the drop-weight of ink droplets as the printhead will operate at closer to the optimum temperature for the specific ink in the printing pass. This will result in a better quality image.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention can be further understood by reference to the following description and attached drawings that illustrate the preferred embodiment. Other features and advantages will be apparent from the following detailed description of the preferred embodiment, taken in conjunction with the accompanying drawings, which illustrate, by way of example, the principles of the invention.

FIG. 1 shows a block diagram of an overall printing system incorporating the present invention.

FIG. 2 is an exemplary printer that incorporates the invention and is shown for illustrative purposes only.

FIG. 3 shows for illustrative purposes only a perspective view of an exemplary print cartridge incorporating the present invention.

FIG. 4 is a schematic cross-sectional view taken through section line 4-4 of FIG. 3 showing the ink chamber arrangement of the print cartridge of FIGS. 1 and 3.

FIG. 5 shows a block diagram of the temperature sensor layout on the printhead incorporated in the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

In the following description of the invention, reference is made to the accompanying drawings, which form a part hereof, and in which is shown by way of illustration a specific example in which the invention may be practiced.

It is to be understood that other embodiments may be utilized and structural changes may be made without departing from the scope of the present invention.

I. General Overview:

FIG. 1 shows a block diagram of an overall printing system incorporating the present invention. The printing system 100 of the present invention includes a printhead assembly 102, ink supply 104 and print media 106. Input data to the printing system 100 comes from the input data channel

108. A temperature controller system 110 is included in the printhead assembly 102. The controller system 110 can be an integrated circuit, firmware, a software printer driver or the like and controls an increase in the mean temperature of the semiconductor wafer or die of the printhead through a feedback loop. The loop activates the heating elements and therefore increases the baseline temperature of the die before printing, and in turn decreases the temperature differential between the baseline temperature and the mean temperature of the die.

II. Exemplary Printing System:

FIG. 2 is a perspective view of an exemplary high-speed large format printing system 200 that incorporates the invention and is shown for illustrative purposes only. The printing system 200 includes a housing 210 mounted on a stand 220. The housing 210 has a left media transport mechanism cover 225 and a right media transport mechanism cover 230 housing a left media transport mechanism (not shown) and a right media transport mechanism (not shown), respectively. A control panel 240 is mounted on the right media transport mechanism cover 230 and provides a user interface with the printing system 200.

A printhead assembly 250 with print cartridges 236 is mounted on a carriage assembly 234, all being shown under a transparent cover 260. The carriage assembly 234 positions the printhead assembly 250 along a carriage bar 265 in a horizontal direction denoted by the "y" axis. A print media 270 (such as paper) is positioned by the media transport mechanism (not shown) in a vertical direction denoted by the "x" axis.

The present invention is equally applicable to alternative printing systems (not shown) such as those incorporating smaller format printers or grit wheel or drum technology to support and move the print media 106 relative to the printhead assembly 102. With a grit wheel design, a grit wheel and pinch roller move the media back and forth along one axis while a carriage carrying one or more printheads scans past the media along an orthogonal axis. With a drum printer design, the media is mounted to a rotating drum that is rotated along one axis while a carriage carrying one or

more printheads scans past the media along an orthogonal axis. In either the drum or grit wheel designs, the scanning is typically not done in a back and forth manner as is the case for the system depicted in FIG. 2.

5 The print cartridges 236 may be removeably mounted or permanently mounted to the scanning carriage 234. Also, the print cartridges 236 can have self-contained ink reservoirs in the body of the printhead (shown in FIG. 3) as the ink supply 104 (shown in FIG. 1). The self-contained ink reservoirs can be refilled with ink for reusing the print cartridges 236. Alternatively, the print cartridges 236 can be each fluidically coupled, via a flexible conduit 240, 10 to one of a plurality of fixed or removable ink containers 242 acting as the ink supply 104 (shown in Fig. 1). As a further alternative, ink supplies 104 can be one or more ink containers separate or separable from print cartridges 236 and removeably mountable to carriage 234.

15 FIG. 3 shows for illustrative purposes only a perspective view of an exemplary printhead assembly 300 (an example of the printhead assembly 102 of FIG. 1) incorporating the present invention. A detailed description of the present invention follows with reference to a typical printhead assembly used with a typical printer, such as printer 200 of FIG. 2. However, the present invention can be incorporated in any printhead and printer 20 configuration.

20 Referring to FIGS. 1 and 2 along with FIG. 3, the printhead assembly 300 is comprised of a thermal head assembly 302 and a printhead body 304. The thermal head assembly 302 can be a flexible material commonly referred to as a Tape Automated Bonding (TAB) assembly. The thermal 25 head assembly 302 contains a flexible nozzle member 306 and interconnect contact pads (not shown) and is secured to the printhead assembly 300. The thermal head assembly 302 can be secured to the print cartridge 300 with suitable adhesives. An integrated circuit chip (not shown) provides feedback to the printer 200 regarding certain parameters of printhead assembly 300. 30 The contact pads align with and electrically contact electrodes (not shown) on carriage 234. The nozzle member 306 preferably contains plural parallel rows of offset nozzles 310 through the thermal head assembly 306 created by, for

example, laser ablation. It should be noted that other nozzle arrangements can be used, such as non-offset parallel rows of nozzles.

III. Component Details:

FIG. 4 is a cross-sectional schematic taken through section line 4-4 of FIG. 3 of the inkjet print cartridge 300 utilizing the present invention. A detailed description of the present invention follows with reference to a typical printhead used with print cartridge 300. However, the present invention can be incorporated in any printhead configuration. Also, the elements of FIG. 4 are not to scale and are exaggerated for simplification.

Referring to FIGS. 1-3 along with FIG. 4, as discussed above, conductors (not shown) are formed on the back of thermal head assembly 302 and terminate in contact pads for contacting electrodes on carriage 234. The other ends of the conductors are bonded to the printhead 302 via terminals or electrodes (not shown) of a substrate 410, such as a semiconductor material, commonly referred to as a die. The substrate or die 410 has ink ejection elements 416 formed thereon and electrically coupled to the conductors. The integrated circuit chip provides the ink ejection elements 416 with operational electrical signals. A barrier layer 412 is located between the nozzle member 306 and the substrate 410 for insulating conductive elements from the substrate 410.

An ink ejection or vaporization chamber 418 is adjacent to each ink ejection element 416, as shown in FIG. 4, so that each ink ejection element 416 is located generally behind a single orifice or nozzle 420 of the nozzle member 306. The nozzles 420 are shown in FIG. 4 to be located near an edge of the substrate 410 for illustrative purposes only. The nozzle 420 can be located in other areas of the nozzle member 306, such as centered between an edge of the substrate 410 and an interior side of the body 304.

Each ink ejection element 416 acts as an ohmic heater when selectively energized by one or more pulses applied sequentially or simultaneously to one or more of the contact pads via the integrated circuit. The ink ejection elements 416 may be heater resistors or piezoelectric elements and for the purposes of the current invention will be heater resistors.

The orifices 420 may be of any size, number, and pattern, and the various figures are designed to simply and clearly show the features of the invention. The relative dimensions of the various features have been greatly adjusted for the sake of clarity.

5 The printhead body 304 is defined by a headland portion 426 located proximate to the back surface of the nozzle member 306 and includes an inner raised support 430. An adhesive layer 432 is located between the back surface of the nozzle member 306 and a top surface of the inner raised support 430 to securely affix the nozzle member 306 to the headland 426.

10 The inner raised support 430 preferably includes an overflow slot 436 for receiving excess adhesive (i.e., adhesive overflow during fabrication of the printhead).

Referring to FIGS. 1-4, during a printing operation, ink stored in an ink reservoir 104 defined by the printhead body 304 generally flows around the edges of the substrate 410 and into the vaporization chamber 418.

5 Energization signals are sent to the ink ejection element 416 and are produced from the electrical connection between the print cartridges 236 and the printer 200. Upon energization of the ink ejection element 416, a thin layer of adjacent ink is superheated.

20 The ideal temperature for ejecting a droplet is about 50 degrees Celsius, but the heating element can reach a temperature of 500 degrees Celsius in 3 microseconds. If the controller fires a number of times in a short period, or the pulse of the firing was lengthened, the heating element would reach a temperature above that required to produce the correct sized ink drop. The energized heater element causes explosive vaporization and, consequently, causes a droplet of ink to be ejected through the orifice or nozzle 420. The vaporization chamber 418 is then refilled by capillary action.

25 This process enables selective deposition of ink on print media 106 to thereby generate text and images. As such, when the printhead assembly 300 is scanned across the print media during printing, variations in the size or physical nature of the ink droplet will affect the location and/or the action of the ejected ink on the print media and therefore affect the quality of printing.

30

A. Controller System

FIG. 5 is a block diagram illustrating the operation and integration of the printhead assembly 102 of FIG. 1. Referring to FIGS 1-4 along with FIG. 5, during a printing operation, ink is provided from the ink supply to an interior portion, such as an ink reservoir 104 of the printhead body 304. The interior portion of the printhead body 304 provides ink to the ink channels 418 for allowing ejection of ink from the vaporization chambers through adjacent nozzles 420. Namely, the printhead assembly 102 receives commands from the controller 110 to print ink based on the input data 108 and form a desired pattern for generating text and images on the print media 106. Print quality of the desired pattern is dependent on accurate placement of the ink droplets on the print media 106.

One way to increase print quality using pigmented inks, is to improve the accuracy and precision of ink droplet formation. This can be achieved by producing droplets at an optimal temperature. In one embodiment, the ideal temperature for ejecting a droplet varies with the ink that is being heated. In this embodiment, the ideal temperature for black ink is 40 degrees centigrade, and 45 degrees centigrade for colored ink. Below these temperatures, the ink drop weight would be lower than that required for an ideal ink droplet. If the temperature rises over 50 degrees centigrade, the risk of nozzle choking through bubble formation becomes a real possibility. The heating element can reach a temperature of 500 degrees centigrade in 3 microseconds. Some control must therefore be exercised to keep temperatures within working limits.

To achieve this, in one embodiment of the present invention, the controller 110 includes a temperature feedback system 530 that defines the baseline operating temperature of the printhead. The temperature feedback system 530 is a controller that receives the temperature of 1 or 1-n digital temperature sensor[s] (DTS) 544. It calculates the temperature or temperatures of a particular die sector or sectors 542 and determines if it is at the threshold temperature for the ink[s] in that sector. If the temperature[s] is below the threshold baseline temperature, the temperature feedback system 530 inactivates the heater element array 540 by switching the gate 536.

When the printing system 100 is activated the trickle warming system 538 is turned on. This trickle warming system 538 remains activated throughout the printing process. A feature of this embodiment is that the various sectors of the die are kept at the optimal temperature, even if they are inactive during the print swath.

The trickle warming system 538 can use any suitable warming device and can include a controller for controlling the electrical current to the firing resistors so that their temperature is below the threshold required to eject an ink drop. This device could be a power field effect transistor [FET]. The FET device provides a capability to warm the printhead assembly to the desired temperature before or during printing operations. This system is referred to as trickle warming system because the printhead assembly 102 allows only a trickle of energy to flow to the firing resistors causing the temperature to rise to the set point.

When the temperature reaches the optimal set point a gate or switch 536 is opened so that the heater element array 540 can be activated. This system allows ink droplets being ejected from an associated ink chamber 522 to be at a preferred temperature for associated flowing ink. The ink droplets will more closely approximate ideal drop weight, so that the ink hue will be more consistent across the print swath. As the die 410 temperature before printing will be higher due to the trickle warming system, the difference between pre-swath temperatures and post swath temperatures will be reduced. This leads to more consistent hue across the print swath. In other words, the difference between the beginning temperatures reached through the trickle warming system 538 and end temperatures of the swath caused by the operation of the pen creates, more consistent hue across the print swath.

B. Temperature Feedback System

Referring to FIGS. 1-5, the input data 108 relates to the actual printed information on the print media 106. Locations of the printed output correspond to the input data 108. Each location represents a small dot in a rectilinear array. The locations vary in size and are related to the pixels of the image of the input data 108 that is to be printed on the print media 106.

Smaller dots in the rectilinear array means that more dots can be printed per inch of the printed media and require a greater number elements in the heater element array 540 being fired.

The input data 108 is received by the image mapping system 512. The image mapping system 512 defines the pixel coordinates, the number and size of pixels to be produced, the colors of each pixel, and the color densities of each pixel. Information regarding pixels that require either black ink or the various colored inks is conveyed to the heater element array 540 through a temperature controlled gate 536. The elements of the heater element array 540 would be specific for the various colors to be printed which could include black and the various combinations of base colors in the cartridges in the printhead[s] 236. The colors that could be printed range from 1-n. The various inks required to produce colors may have differing baseline set points, 1-n, 534.

DTS region sensors[1-n] 544 sense the temperature of the heater elements on the heater element array 540 through the die body 542. The DTS region sensors, 1-n, 544 reflect the temperatures of the various heater elements, 1-n, 540 that heat the chambers in the ink chamber array [1-n] 522 for the various inks. The temperature feedback analyzer 532 monitors and observes temperatures of the DTS region sensors 544.

Information from the DTS sensors 544 is directed to the baseline set point [1-n] 534. The baseline set point 1-n 534 activates respective trickle warming systems 1-n 538 if any measured temperature is below the threshold determined for that particular ink. As the printer continues to print, the temperature feedback analyzer 532 continues to monitor the temperature through the DTS sensors 544 and adjusts the trickle warming system, 1-n, 538 accordingly, until the plot is finished. The trickle warming system 538 warms the die 542 to the threshold temperature, and at this point the DTS region sensor 544 forwards the temperature to the temperature feedback analyzer 532 which opens the gate 536. This in turn activates the respective elements in the heater element array 540.

The heater elements will heat and ink in the respective chamber array 522 will vaporize. Black ink droplets closer to optimal weights will be ejected

from the black nozzles in the nozzle array 524 to the print media 106. Similarly, color droplets are produced on the print media 106 from the color nozzles in the nozzle array 524.

5 IV. Conclusion

10 In conclusion, with the system and method of the present invention, a dynamic and proactive printhead assembly is established through the temperature feedback system 530. This helps maintain the die at an optimum temperature for producing droplets in pigmented inks. The net effect of this invention is that a better quality of droplet will be produced. Consequently, the controller 110 maintains the printhead assembly 102 at a mean temperature that more closely approximates the optimal temperature for the formation of ink droplets. As such, activation of the trickle warming system [1-n] 538 is conducted in a more efficient and effective manner. The heater element array 540, and the nozzle array 524 create a pattern of ink droplets across a large swath. The reproduction of the image on the print media 106 based on the input data 108 would have less hue shifts across the swath.

15 The foregoing has described the principles, preferred embodiments and modes of operation of the present invention. However, the invention should not be construed as being limited to the particular embodiments discussed. The above-described embodiments should be regarded as illustrative rather than restrictive, and it should be appreciated that variations may be made in those embodiments by workers skilled in the art without departing from the scope of the present invention as defined by the following claims.

20

25